

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804


Owner of the Declaration	EPAQ
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-EPQ-20130169-CBG1-EN
Issue date	12.09.2013
Valid to	11.09.2018

Double skin steel faced sandwich panels with a core made of mineral wool EPAQ




www.bau-umwelt.com



Institut Bauen
und Umwelt e.V.



General Information

<p>EPAQ</p> <hr/> <p>Programme holder IBU - Institut Bauen und Umwelt e.V. Panoramastraße 1 D-10178 Berlin</p> <hr/> <p>Declaration number EPD-EPQ-20130169-CBG1-EN</p> <hr/> <p>This Declaration is based on the Product Category Rules: Double skin metal faced sandwich panels, 07-2013 (PCR tested and approved by the independent expert committee [SVA])</p> <hr/> <p>Issue date 12.09.2013</p> <hr/> <p>Valid to 11.09.2018</p> <hr/> <p> Prof. Dr.-Ing. Horst J. Bossenmayer (President of Institut Bauen und Umwelt e.V.)</p> <hr/> <p> Prof. Dr.-Ing. Hans-Wolf Reinhardt (Chairman of SVA)</p>	<p>Double skin steel faced sandwich panels with a core made of mineral wool</p> <hr/> <p>Owner of the Declaration EPAQ Max-Planck-Straße 4 D-40237 Düsseldorf</p> <hr/> <p>Declared product / Declared unit 1m² prefabricated double skin steel faced sandwich panels with a insulating core made of mineral wool</p> <hr/> <p>Scope: The purpose of this document is limited to continuously produced sandwich panels with face sheets made of steel that are manufactured by member companies of EPAQ. Data has been provided by 8 member companies of EPAQ for the year 2011. These companies represent between 50% and 62% of EPAQ members producing sandwich panels. Production volume of these companies is about 50% to the European market. The owner of the declaration shall be liable for the underlying information and evidence.</p> <hr/> <p>Verification</p> <table border="1"> <tr> <td colspan="2">The CEN Norm EN 15804 serves as the core PCR</td> </tr> <tr> <td colspan="2">Independent verification of the declaration and data according to ISO 14025</td> </tr> <tr> <td><input type="checkbox"/> internally</td> <td><input checked="" type="checkbox"/> externally</td> </tr> </table> <hr/> <p> Matthias Schulz (Independent tester appointed by SVA)</p>	The CEN Norm EN 15804 serves as the core PCR		Independent verification of the declaration and data according to ISO 14025		<input type="checkbox"/> internally	<input checked="" type="checkbox"/> externally
The CEN Norm EN 15804 serves as the core PCR							
Independent verification of the declaration and data according to ISO 14025							
<input type="checkbox"/> internally	<input checked="" type="checkbox"/> externally						

Product

Product description and placing on the market

Prefabricated double skin steel faced sandwich panels with a core made of mineral wool used for load-bearing, self-supporting and non-supporting application in roof, wall and ceiling structures.

The profiled internal and external steel sheets are made of a core of steel, which is protected against corrosion with zinc and organic coatings. The thermal insulating core material is made of mineral wool according to /EN 13162/ with sealing tapes according to /DIN 18542/. The core is linked on both sides with resistance to shear forces to the profiled steel sheets.

The LCA is based on vertical averaging of the specific producer datasets under consideration of the respective yearly production amounts.

The products must comply with the Regulation (EU) No 305/2011 taking into account the harmonised technical specification; they may be put on the market with the Declaration of Performance and the CE-mark.

Application

Application as covering components in roof and wall structures for mainly static loads.

Sandwich panels in wall and roof application overtake tasks of the building physics, especially sound, heat and moisture safely. They perform simultaneously the function of air tightness of the building envelope.

The application takes place according to national regulations.

Technical Data

Technical specifications for sandwich panels with a core made of mineral wool are:

- /EN 14509/
- /EN 13162/

Constructional data

Name	Value			Unit
	50	100	200	
Density of the insulation	115-120			kg/m ³
Thickness of the element. When the outer layers are flat, this is the overall height of the element (D); on heavily profiled elements this is the consistent core thickness without profile (dc)	50	100	200	mm
Thickness of the outer layer	0,6	0,6	0,6	mm

Name	Value			Unit
	50	100	200	
Thickness of the inner layer	0,5	0,5	0,5	mm
Calculation value for thermal conductivity of the insulation	0,0440	0,0440	0,0440	W/(mK)
Heat transfer coefficient of the total Element incl. heat bridges due to overlap and fixing elements	0,8115	0,4467	0,2196	W/(m ² K)
Weight	14,6	20,4	32,4	kg/m ²

Base materials / Ancillary materials

Composition of the sandwich panels:

material	Thickness of the element		
	50mm	100mm	200mm
Steel sheet	61%	43%	29%
Thermal insulation core	36%	55%	70%
adhesive	3%	2%	1%

Steel according to /EN 10169/:

S 280 GD to S 320 GD

Metallic coating according to /EN 10346/:

Zinc Z 275, coating 275 g/m². The zinc layer has a

content of at least 99 weight percent zinc and typical thickness of 20 µm.

Organic coating according to /EN 12944-1/:

Polyester (SP), coil coating, 25 µm on the application side and max.15 µm on the back side.

Thermal insulation core according to /EN 13162/:

mineral wool

The thermal insulating core is bonded with an organic adhesive between the steel sheets.

The panels contain sealing tapes (amount on total weight < 0,1%) according to DIN 18542.

No /REACH/ materials included.

Reference service life

Double skin steel faced sandwich panels with the use in lightweight metal constructions must withstand a term of protection of at least 15 years minimum. The term of protection is the period until first slight renewals in the surface are needed, only if there is no need of frequently inspections and service.

The term of protection depends on the location, weather conditions and the quality of the coating.

Double skin steel faced sandwich panels exhibit an estimated service life of 40 – 45 years depending on the use conditions.

LCA: Calculation rules

Declared Unit

The declared unit is 1 m² of sandwich element. The averaging is done vertically based on the specific primary data.

Declared unit

MW 50 mm	Value	Unit
Declared unit	1	m ²
Surface weight	14,6	kg/m ²
Conversion factor to 1 kg	1/14,6	-
MW 100 mm	Value	Unit
Declared unit	1	m ²
Surface weight	20,4	Kg/m ²
Conversion factor to 1 kg	1/20,4	-
MW 200 mm	Value	Unit
Declared unit	1	m ²
Surface weight	32,4	Kg/m ²
Conversion factor to 1 kg	1/32,4	-

System boundary

Type of the EPD: cradle to gate - with options

Production stage (modules A1-A3) includes processes that provide materials and energy input for the system, manufacturing and transport processes up to the factory gate, as well as waste processing.

For the end of life it is assumed that the steel proportion is recycled with credit for the recycling potential (declared in module D) and the MW proportion is landfilled (declared in module C4).

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account

LCA: Scenarios and additional technical inform

The following technical information is a basis for the declared modules.

End of life (C1-C4)




Name	Value			Unit
	50	100	200	
Recycling	8,9	8,8	9,4	kg
Energy retrieving	0	0	0	kg
Landfilling	5,7	11,8	23,0	kg

LCA: Ergebnisse

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES	
Raw material supply	Transport	Manufacturing	Transport	Construction-installation process	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recycling-Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
X	X	X	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	MND	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 m² Sandwich panel

		 MW 50 mm			 MW 100 mm			 MW 200 mm		
Parameter	Unit	A1 - A3	C4	D	A1 - A3	C4	D	A1 - A3	C4	D
GWP	[kg CO ₂ -Äq.]	30,1	0,3	-13,6	37,6	0,7	-13,7	53,3	1,3	-13,9
ODP	[kg CFC11-Äq.]	4,22E-08	5,96E-11	1,02E-09	1,33E-08	1,21E-10	1,03E-09	6,18E-09	2,48E-10	1,04E-09
AP	[kg SO ₂ -Äq.]	0,134	0,001	-0,052	0,182	0,001	-0,053	0,273	0,002	-0,053
EP	[kg PO ₄ ³⁻ -Äq.]	1,32E-02	7,26E-05	-4,34E-03	1,88E-02	1,48E-04	-4,39E-03	2,87E-02	3,02E-04	-4,43E-03
POCP	[kg Ethen Äq.]	1,44E-02	1,23E-04	-7,77E-03	1,81E-02	2,51E-04	-7,85E-03	2,58E-02	5,12E-04	-7,93E-03
ADPE	[kg Sb Äq.]	1,76E-03	2,79E-08	-3,68E-07	1,75E-03	5,67E-08	-3,72E-07	1,86E-03	1,16E-07	-3,75E-07
ADPF	[MJ]	369,0	1,0	-127,0	453,2	2,1	-128,0	642,7	4,3	-130,0
Caption	GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non fossil resources; ADPF = Abiotic depletion potential for fossil resources									

RESULTS OF THE LCA - RESOURCE USE: 1 m² Sandwich panel

		MW 50 mm			MW 100 mm			MW 200 mm		
Parameter	Unit	A1 - A3	C4	D	A1 - A3	C4	D	A1 - A3	C4	D
PERE	[MJ]	20,0	-	-	24,8	-	-	36,7	-	-
PERM	[MJ]	0	-	-	0	-	-	0	-	-
PERT	[MJ]	20,0	0,1	2,1	24,8	0,2	2,1	36,7	0,3	2,1
PENRE	[MJ]	371,5	-	-	454,8	-	-	649,7	-	-
PENRM	[MJ]	16,6	-	-	25,4	-	-	39,2	-	-
PENRT	[MJ]	388,0	1,1	-119,0	480,2	2,2	-121,0	688,9	4,5	-122,0
SM	[kg]	0	-	-	0	-	-	0	-	-
RSF	[MJ]	0	0	0	0	0	0	0	0	0
NRSF	[MJ]	0	0	0	0	0	0	0	0	0
FW*	[m ³]	-	-	-	-	-	-	-	-	-
Caption	PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non renewable secondary fuels; FW = Use of net fresh water									

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES: 1 m² Sandwich panel

		MW 50 mm			MW 100 mm			MW 200 mm		
Parameter	Unit	A1 - A3	C4	D	A1 - A3	C4	D	A1 - A3	C4	D
HDW*	[kg]	-	-	-	-	-	-	-	-	-
NHDW*	[kg]	-	-	-	-	-	-	-	-	-
RWD*	[kg]	-	-	-	-	-	-	-	-	-
CRU	[kg]	0	-	0	0	-	0	0	-	0
MFR**	[kg]	0	-	8,3	0	-	8,4	0	-	8,5
MER	[kg]	0	-	0	0	-	0	0	-	0
EEE [Typ1]	[MJ]	0	0	-	0	0	-	0	0	-
EET [Typ2]	[MJ]	0	0	-	0	0	-	0	0	-
Caption	HDW = Hazardous waste disposed; NHDW = Non hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy									

*The inventories do not support the methodological approach for the declaration of water and waste indicators. The material amounts, displayed with these inventories contribute significantly > 3% (referring to the mass of the declared unit). The indicators are not declared (decision of IBU advisory board 2013-01-07).

** No credit is given for the amount of recycled steel entering load free the system.

References

Institut Bauen und Umwelt e.V., (Ed.):

General principles

for the EPD range of Institut Bauen und Umwelt e.V. (IBU), 2011-06.

PCR Part A

Product Category Rules for Construction Products. Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report, 2013-07.

PCR Part B

Product Category Rules for Construction Products Part B: Requirements on the EPD for Thin walled profiles and profiled panels of metal, 2013-07.

www.bau-umwelt.com

AgBB

Committee for Health-related Evaluation of Building Products (Ausschuss zur gesundheitlichen Bewertung von Bauprodukten)

ISO 14025:2011-10: Environmental labels and declarations – Type III environmental declarations – Principles and procedures

EN 15804:2012-04: Sustainability of construction works – Environmental Product Declarations – Core rules for the product category of construction products

DIN 18542:2009-07, Sealing of outside wall joints with impregnated sealing tapes made of cellular plastics - Impregnated sealing tapes - Requirements and testing

EN 10169:2012-06, Continuously organic coated (coil coated) steel flat products - Technical delivery conditions

EN 10346:2009-07, Continuously hot-dip coated steel flat products - Technical delivery conditions

EN 13162:2013-03, Thermal insulation products for buildings - Factory made mineral wool (MW) products – Specification

EN 13501-1: 2010-01, Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

EN 14509:2009-04 Self-supporting double skin metal faced insulating panels, Factory made products, Specifications

EN ISO 12944:1998-07, Paints and varnishes - Corrosion protection of steel structures by protective paint systems

GaBi 6: Software and databasis for Life Cycle Engineering. LBP, University of Stuttgart and PE International. 2013.

GaBi Documentation: Documentation of the GaBi 6 datasets. LBP, University of Stuttgart and PE International. 2013. <http://documentation.gabi-software.com/>

EPAQ European Quality Regulations for Panels

REACH - Regulation concerning the Registration , Evaluation , Authorisation and Restriction of **CH**emicals

Following companies are represented with their products in this EPD:



 Institut Bauen und Umwelt e.V.	<p>Publisher Institut Bauen und Umwelt e.V. Panoramastraße 1 10178 Berlin Germany</p> <p>Tel +49 30 30 877 49-0 Fax +49 30 30 877 49-29 Mail info@bau-umwelt.com Web www.bau-umwelt.com</p>
 Institut Bauen und Umwelt e.V.	<p>Programme holder Institut Bauen und Umwelt e.V. Panoramastraße 1 10178 Berlin Germany</p> <p>Tel +49 30 30 877 49-0 Fax +49 30 30 877 49-29 Mail info@bau-umwelt.com Web www.bau-umwelt.com</p>
	<p>Owner of the Declaration EPAQ Max-Planck-Straße 4 40237 Düsseldorf Germany</p> <p>Tel +49 211 69 89 4 11 Fax +49 211 67 20 34 Mail info@epaq.eu Web www.EPAQ.eu</p>
	<p>Author of the Life Cycle Assessment PE International AG Hauptstraße 111 70771 Leinfelden-Echterdingen Germany</p> <p>Tel +49 711 34 18 17-0 Fax +49 711 34 18 17-25 Mail info@pe-international.com Web www.pe-international.com</p>